



EUREKANOL W2

COMPOSITION :

EUREKANOL W2 IS SULFITED OIL WITH VERY GOOD BLEACHING, FILLING AND SOFTENING WITH WAXY FEEL ON THE GRAIN.

EUREKANOL W2 HAS GOOD STABILITY AND THUS IS STABLE FOR NEUTRALIZING BATH AND MAIN FATLIQUORING BATH.

APPLICATION :

- A. WHITE NAPPA LEATHER
- B. WHITE GLOVING LEATHER
- C. WHITE LINING LEATHER
- D. DYEING OF PASTEL SHADE LEATHER
- E. WHITE SHOE UPPER
- F. LIGHT COLOR UPHOLSTERY LEATHER

PROPERTIES :

APPEARANCE :	LIGHT YELLOWISH PASTE
ANALYSIS :	pH 5.5 - 6.5
ACTIVE INGREDIENTS :	55 - 58 %
STABILITY:	EUREKANOL W2 IS APPLICABLE AFTER RECHROMING, NEUTRALIZING, AND FATLIQUORING BATH.
IONIC CHARGE:	ANIONIC

PACKING : 120KGS, 150 KGS PLASTIC DRUMS

NOTE : STIR WELL BEFORE USE
DUE TO NATURE OF FAT USED, THERE MIGHT BE SOME WAX CRYSTAL IN THE WINTER TIME

VERY SUPPLE LEATHER:

AFTER RECHROMING:

WASH: 100 - 150% WATER 45C 10' X 3

PREFATLIQUORING: 100 - 150% WATER 45C

'2 - 4% EUREKANOL W2 RUN TILL EXHAUST

THEN PROCEED WITH NEUTRALIZATION AND IN NEUTRALIZATION BATH, 2 - 4% OF LEATHERNOL JOBA- LE COULD BE APPLIED, WITH THE REST IN MAIN FATLIQUORING BATH.